# HAIR DRYERS GW02 03 01 00 Hair dryer 1.400W





## **Product description**

Pistol-type hot air hair dryer with wall mount Features two shaver sockets at 110 and 230V Built-in general switch Two airflow speeds/three temperature options ON/OFF safety switch White ABS casing with chrome features Suitable for hotel rooms

## **Technical specifications:**

Pistol-type hot air hair dryer with wall mount. Both the mount and the hair dryer are made in white ABS plastic. The mount is fixed to the wall with two screws, for which two holes need to be drilled in the wall using a 6 mm drill bit. On the front of the hair dryer mount, there is a main switch with an indicator light and two shaver sockets, a 110V flat pin and the other a 230V round or flat pin. On the front of the pistol-type handle, there is a switch with three positions: 'C' – minimum flow/cold air, '1' – minimum flow/hot air and '2' maximum flow/hot air. To use the hair dryer continuously, the spring push button located on the back of the handle must be pressed and held down. This stops the hair dryer from being switched on accidentally. It has a 10000 r.p.m. DC motor that delivers an airflow of 75 m3/h at a speed of 55 km/h. The heating element is 1360W – 230V, with a heat limiter. The total power rating is 1400W at 230V – 50/60Hz. The protection class against splashing is IPX1. Class II. The total measurements of the hair dryer are 280 x 240 x 150 mm, and its total net weight is 1.2 kg. The hair dryer model is GW02 03 01 00, manufactured by GENWEC WASHROOM S.L. - Av. Joan Carles I, 46-48 - c.p: 08025 L'Hospitalet de Llobregat. www.genwec.com.

### **Technical characteristics**

#### **Electrical specifications**

Voltage/Frequency: 220-240V 50/60 Hz

Total power rating: 1400 W Heating element rating: 1360 W Motor power rating: 40 W

Motor type: DC

Rotor speed: 10000 r.p.m. Electrical insulation: Class II Protection class: IPX1 Overheat thermostat. (Automatic reset)

One 110V flat pin shaver socket

One 220V flat and round pin shaver socket

#### Mechanical specifications

Air flow: 75 m<sub>3</sub>/h Air speed: 55 km/h

Hair dryer and mount in white ABS thermoplastic.

Chrome fittings on hair dryer.
Protective grill in polycarbonate.
Power cable with plug from mount.
Hair-dryer to mount with spiral flex cable.

Illuminated general switch on the bottom of the mount.

Position switch on the hair dryer support. Possibility of choosing between two voltages.

ON/OFF safety switch. Avoids improper use of the hair dryer.

# **Packaging specifications**

- Type of individual package: Single cardboard box with a plastic bag
- Dimensions of individual package: 270 x 220 x 115 mm
- Weight of individual package: 1.5 Kg
- Product dimensions: 280 x 240 x 150 mm
- Product weight: 1.2 kg
- Units per box: 12
- Units per pallet: 96 (\*)

(\*) Height below 1.1 m.

 ${\sf GENWEC\ WASHROOM\ S.L.\ } \textit{reserves\ the\ right\ to\ modify\ and/or\ rectify\ the\ products\ and\ their\ specifications\ without\ prior\ notice$ 

Dimensions: ± 3%

Reviewed by: EJO\_v1 (02/2015)