



ARTICULO: 2295 **Purgador Bimetálico con filtro** ***Bimetalic steam trap with strainer***

Características	Features
1. Purgador Bimetálico en acero al carbono. 2. Diseño Compacto. 3. Filtro incorporado. 4. Alta durabilidad y fácil mantenimiento. 5. Excelente eliminación de aire 6. Aplicación: Drenaje de Líneas de Vapor 7. Extremos roscados según ISO 228/1. Condiciones de Trabajo: Máxima presión de Diseño del cuerpo: PN40. Presión máxima admisible (PMA) 38 bar. Temperatura máxima admisible (TMA): 300°C. Máxima presión diferencial: 35 bar. Instalación en tubería horizontal (recomendado).	1. Carbon Steel Bimetalic steam trap. 2. Compact structure. 3. With strainer. 4. High durability and easy maintenance. 5. Excellent air discharge. 6. Application: Steam pipelines drainage. 7. Threaded ends according to ISO 228/1. Working Conditions: Body design conditions: PN40. Maximum allowable pressure (PMA): 38 bar. Maximum allowable temperature (TMA): 300°C. Maximum differential pressure: 35 bar. The preferred installation is in horizontal position.



PARTES COMPONENTES – COMPONENT PARTS:

Nº	Nombre / Name	Material
1	Tapa / Cover	Acero Carbono A105 / Carbon Steel A105
2	Cuerpo / Body	Acero Carbono A105 / Carbon Steel A105
3	Eje válvula / Valve stem	Acero Inoxidable 420 / Stainless Steel 420
4	Tuerca / Nut	Acero Inoxidable 304 / Stainless Steel 304
5	Bimetálico / Bimetalic	-----
6	Asiento / Seat	Acero Inoxidable 420 / Stainless Steel 420
7	Junta / Gasket	Ac. Inox 304 + Grafito / S.S. 304 + Graphite
8	Malla Filtro / Strainer Screen	Acero Inoxidable 304 / Stainless Steel 304
9	Tapón inferior / Bottom Plug	Acero Carbono A105 / Carbon Steel A105

DIMENSIONES – DIMENSIONS:

Ref.	Medida / Size	Dimensiones / <i>Dimensions</i>				Peso / Weight (Kg)
		H	h	B	L	
2295 04	DN15	150	64	98	95	1,750
2295 05	DN20	152	66	98	95	1,950
2295 06	DN25	154	68	98	95	2,200

CAPACIDAD DE DESCARGA – DISCHARGE CAPACITY:

