


CM64111 32 41

COLUMNA MONOMANDO EXTENSIBLE CON KIT KORAL KORAL SINGLE LEVER EXTENSIBLE COLUMN WITH KIT



Descripción / Description

Columna monomando extensible con kit acabado negro mate de alta calidad.

Se suministra con rociador orientable, mango de ducha con 3 funciones, soporte de ducha deslizante y orientable y flexo de ducha de 1.5 metros de acero inoxidable.

Esta columna posee un sistema innovador al incluir la función de inversor en el propio cartucho, evitando de esta manera un inversor externo o un segundo mando.

Deja que el agua acaricie todos tus poros, y disfruta de las sinuosas líneas y el estilo propio de la nueva Serie Koral.

Single lever extensible column with kit high quality black mate finish.

Supplied with adjustable shower head, 3-function shower handle, adjustable sliding shower bracket and 1.5meter flexible hose in stainless steel.

This column has a system by including the inverter function in the cartridge, to avoid an external inverter or a second control.

Let the water caress all your pores and enjoy the sinuous lines of the new Koral Series.

Características

- 1) Fabricada en latón según UNE-EN 1982.
- 2) Maneta realizada en Zamak.
- 3) Acabado negro mate.
- 4) Cartucho 2 vías.
- 5) Soporte deslizante y orientable.
- 6) Regulable en altura
- 7) Suministrada con flexo de ducha de acero inoxidable negro mate de 1,5 m, rociador orientable con jet anticalcáreo y mango de ducha con 3 funciones.
- 8) Temperatura máxima: 85 °C.
- 9) Temp. máx. recomendada: 65 °C.
- 10) Presión máxima: 10 bar.
- 11) Presión mínima: 0,5 bar.
- 12) Presión recomendada: 1 - 3 bar.

Features

- 1) Made in brass according to UNE-EN1982.
- 2) Lever made in Zamak.
- 3) Black mate finish.
- 4) 2-way cartridge
- 5) Sliding and adjustable rotary holder.
- 6) Adjustable in height
- 7) Fitted with 1.5 m. Black mate stainless steel flexible hose, adjustable sprayer with anti-lime jets and 3 functions hand shower.
- 8) Maximum temperature: 85 °C.
- 9) Max. recommended temp.: 65 °C.
- 10) Maximum pressure: 10 bar.
- 11) Minimum pressure: 0,5 bar.
- 12) Recommended pressure: 1 - 3 bar.

Funciones columna / Column functions




Rociador antical
Anti-lime jets shower head




Rociador orientable
Adjustable shower head




Rociador Ø220 mm.
Ø220 mm. round shower head



Mango de ducha
antical
Anti-lime jets shower head




Flexo doble grapaje
Double lock flexible hose



Regulación en profundidad
Depth regulation



Regulación lateral
Side regulation



Soporte regulable en altura
Height regulable holder



Soporte inclinable
Bending holder



Barra telescópica
Telescopic sliding bar

Funciones mango de ducha / Handshower functions

1



Lluvia fina / *Thin rain jet*

2




Lluvia fina + hidromasaje
Thin rain + hydro-massage jet

3




Hidromasaje
Hydro-massage jet




Caudal / Water Flow

Presión/ Pressure		Caudal / Water Flow			
		Rociador/ Shower	Ducha / Hand Shower		
			Pos. 1	Pos. 2	Pos. 3
Bar	Psi	l/min	l/min	l/min	l/min
0,5	7,3	5,5	3,6	4,2	3
1	14,5	7	5	5,6	4,2
1,5	21,8	8,1	6,1	6,8	5,1
2	29,0	9,3	7,2	8	6
2,5	36,3	10,3	8,1	9	7
3	43,5	11,2	9	9,8	7,8
3,5	50,8	12	9,8	10,6	8,5
4	58,0	12,8	10,6	11,4	9,2
4,5	65,3	13,5	11,3	12,2	9,8
5	72,5	14,3	12	13	10,4
5,5	79,8	14,9	12,6	13,6	10,9



Recambios / Spare Parts

No.	Código	Descripción / Description
1	R65112 41	Rociador D22 Oslo Negro <i>Black Oslo D22 shower head</i>
2	DXL3 41	Mango de ducha 3 jets Negro <i>Black 3 jets hand shower</i>
3	9908 0367	Soporte deslizante columna Negro <i>Black column sliding shower holder</i>
4	9908 0368	Flexo H 1/2" - H 1/2" 1,5 m Negro <i>F 1/2" - F 1/2" 1.5 m Black flexible hose</i>
5	9908 0366	Soporte columna Negro <i>Black column holder</i>
6	J17	Set de juntas columna extensible <i>Extensible column gasket set</i>
7	5CM64111 41	Cuerpo monomando columna Koral <i>NegroBlack Koral column single handle body</i>
8	100058	Cartucho cerámico 2 vías <i>2-way ceramic cartridge</i>
9	100001T 32 41	Maneta 2p Koral Negra <i>Black 2p Koral lever</i>
10	100126 41	Conjunto florón y excentricas redondo Negro <i>Black Round scutcheon and eccentric set</i>



Calidad de los productos Genebre en grifería / *Genebre general quality in taps*

La grifería GENE BRE está diseñada y fabricada según los estándares europeos de calidad, como la UNE-EN 19703 ofreciendo así al cliente la funcionalidad, durabilidad y seguridad esperadas.

El latón empleado en nuestros cuerpos y componentes pertenece a las aleaciones CC754S según norma EN 1982 y CW617N según norma EN 12165. Las superficies cromadas cumplen la norma EN 248, resistencia a la niebla salina 5% (NaCl), Ph 6,5 T 36°C. según ISO 9227.

Los atomizadores cuentan con casquillos en latón cromado resistente a la corrosión y cartucho aireador en plástico anti calcáreo, según lo especificado en la norma EN 246.

Utilización de cartuchos mezcladores con discos cerámicos de alta calidad fabricados en Al₂O₃ 99%, según normas EN 200 y NF 077 capaces de resistir más de 200.000 maniobras y ofrecer la suavidad y estanqueidad originales.

Los sistemas de giro de los caños han sido fabricados según norma EN 817, siendo capaces de resistir más de 80.000 maniobras.

Empleamos válvulas anti retorno en mezcladores termostáticos según norma EN1717 a fin de asegurar la no intercomunicación.

Todos los cartuchos termostáticos están dotados de un sistema de seguridad anti escaldamiento según norma EN 1111.

Nuestros mangos de ducha están fabricados según norma EN 1112 y los Flexos de ducha fabricados según norma EN 1113. Las Conexiones flexibles según norma UNE EN 13618.

A fin de asegurar el cumplimiento de estas normas la empresa GENE BRE posee diferentes certificaciones: ISO 9001 Sistema de Gestión de la Calidad. ISO 14001 Sistema de Gestión Ambiental.

GENEBRE posee productos homologados por el Ministerio de Industria y Energía de España.

Conexiones usadas en nuestros productos fabricadas según UNE EN 13618

Certificación de mecanismos y componentes en laboratorios acreditados por ENAC.

Genebre posee productos certificados por el Laboratorio Oliver Rodés, confirmando el cumplimiento de los criterios sanitarios de la calidad del agua para el consumo humano (RD 140/2003 de 07 de febrero (legislación española) y de la directiva europea relativa a la calidad de las aguas destinadas del consumo humano.

La garantía de los productos GENE BRE está mundialmente reconocida.

Ofrecemos un servicio de asistencia técnica, así como de resolución de incidencias.

GENEBRE's taps are designed and manufactured in compliance with European standards, such as UNE-EN 19703, to comply with and exceed the European Product Directives, thereby offering customers the desired functionality, durability and safety.

The brass used for our taps and components is according to CC754S alloy, in compliance with standard EN 1982 and CW617N alloy in compliance with standard EN 12165.

Chromed surfaces are in compliance with EN 248, resistant to 5% salt spray (NaCl), PH 6.5 T 36°C, in compliance with standard ISO 9227.

Aerators have chrome-plated brass casings resistant to corrosion and plastic anti-lime scale aerator cartridges, in compliance with standard EN 246.

Use of mixing cartridges with high-quality ceramic discs manufactured in Al₂O₃ 99%, in compliance with standards EN 200 and NF 077 capable of withstanding more than 200,000 manoeuvres and offering the original softness and water tightness.

The rotation systems of the water spouts have been manufactured in compliance with standard EN 817 and are capable of withstanding more than 80,000 manoeuvres.

We use anti-backflow valves in thermostatic mixers in compliance with standard EN1717 to ensure there is no backflow.

All thermostatic cartridges are fitted with an anti-scalding security system in compliance with standard EN 1111.

Our handshowers are manufactured in compliance with standard EN 1112 and the Shower hoses are manufactured in compliance with standard EN 1113. The flexible connections in compliance with standard UNE EN 13618.

By means of ensuring these standards are complied with, the company GENE BRE hold different certifications: ISO 9001 Quality management system and ISO 14001 Environmental management system.

GENEBRE owns products approved by the Spanish Ministry of Industry and Energy.

Connections used in our products manufactured according to UNE 13618.

Certification of mechanisms and components in ENAC-accredited laboratories.

Genebre owns products certified by the Laboratory Oliver Rodés, confirming compliance with the sanitary criteria for the quality of water for human consumption (RD 140/2003 dated 7 February – Spanish legislation) and European Directive relating to the quality of water intended for human consumption.

The guarantee of GENE BRE's products is internationally recognized.

We provide a technical assistance service, as well as an incident resolution service.